

Sealer Rejuvenator

INNOTECH SEALER REJUVENATOR is a specially formulated blend of solvents designed specifically for use with decorative concrete acrylic sealers.

Product Features and Benefits

INNOTECH SEALER REJUVENATOR ...

- Is an excellent product for:
 - Bringing the gloss back to Imprinted or colored concrete sealed with acrylic sealers
 - Re-emulsifying acrylic sealers that did not chemically bond during the resealing application.
 - Emulsifying acrylic sealers that have moisture trapped under the surface
 - Doing a solvent wash on previously sealed surfaces to enhance the adhesion of the next sealer coat
 - Using it for cleaning sprayers and tools used in applying acrylic sealers
- Increases the gloss and durability of sealed concrete surfaces.
- Will not cause the sealer to yellow, haze or flake.

Prior to Application

- The surface should be clean and dry.
- This material is dependent on proper penetration of the existing sealer application. Any existing oils, paints, dirt and/or efflorescence will inhibit penetration of INNOTECH SEALER REJUVENATOR. Any materials that would prevent penetration must be removed before application. Use INNOTECH CONCRETE DEGREASER & NEUTRALIZER† (dilute 4-oz. of product to 1-gallon of water, or 2.5-cups of product to 5-gallons of water) to help remove grease and oil. Harsh chemicals should never be used to remove any of the materials cited here.
- Prior to product application, test INNOTECH SEALER REJUVENATOR in an inconspicuous area for desired results.

Product Application: Previously Sealed Concrete

- For smooth-troweled sealed concrete, a smooth concrete sprayer or tight nap roller is recommended. For rough surfaces or textured concrete, a ¾-inch to ½-inch nap roller is recommended. For small areas, a low nap roller may be used without the sprayer. Apply the INNOTECH SEALER REJUVENATOR uniformly. Important: When applying INNOTECH SEALER REJUVENATOR, do not allow the sealer to puddle. Apply the INNOTECH SEALER REJUVENATOR as uniformly as possible, without leaving either spaces or puddles.
- The INNOTECH SEALER REJUVENATOR will cause the existing sealer to return to its original liquid form.
- The sealer will dry again in a few hours and return to its gloss.

Coverage Information

Coverage rates may vary depending on the texture, porosity and condition of the concrete, application method, and other local conditions.

- Approximately 200 sq.ft. per gallon.

Maintenance

INNOTECH highly recommends you develop and follow a schedule of routine maintenance for all colored concrete, so it maintains a quality appearance. Colored concrete installations should be routinely inspected, cleaned and resealed as required by the local conditions. Cleaning and resealing schedules will depend on a number of factors including, but not limited to, volume and intensity of traffic, maintenance procedures and weather.

Production Limitations

INNOTECH SEALER REJUVENATOR is not a curing or sealing compound.

- Do not apply INNOTECH SEALER REJUVENATOR to existing sealed surfaces that have yellowed.
- INNOTECH SEALER REJUVENATOR is highly flammable and care must be taken in the use, handling and storage of this product to keep it away from sources of ignition.
- Inadequate coverage will dramatically reduce the performance of INNOTECH SEALER REJUVENATOR.
- Failure to remove dirt and debris from the surface or failure to properly clean the surface will result in the product failing to properly interact with the sealed surface.
- Do not apply INNOTECH SEALER REJUVENATOR if the surface or ambient temperature is below 45 °F, above 90 °F, or if the temperature is expected to fall below freezing (32 °F) within the 24-hour curing cycle. Do not apply if rain is imminent.

Dry Time

Drying times will vary depending on surface porosity, temperature, humidity and local conditions.

- Set to Touch: Surface can be lightly touched 30-45 minutes following application.
- Recoat: Surface can be recoated 1-2 hours after each application.
- Light Foot Traffic: Light pedestrian traffic can be allowed eight to twelve hours after final coat.
- Vehicle Traffic: Vehicle traffic can be allowed in 48 hours.

Available Packaging

INNOTECH SEALER REJUVENATOR is available in 5-gallon containers.

Product Shelf Life/Storage

Store INNOTECH SEALER REJUVENATOR indoors, away from heat or sunlight, or sources of ignition at a temperature range of 50 °F - 80 °F. Do not allow product to freeze. Shelf life: 12 months.

Product Handling

Prior to using INNOTECH SEALER REJUVENATOR please reference the corresponding Safety Data Sheet to ensure safe handling. Always wear gloves and eye protection when handling product.

Product Warranty

INNOTECH SEALER REJUVENATOR is a proprietary product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed or implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact INNOTECH with any questions regarding this policy.

PLEASE REFER TO CORRESPONDING TECHNICAL BULLETIN FOR PRODUCT AND APPLICATION DATA.

INNOTECH SEALER REJUVENATOR and other INNOTECH products are for professional use only.

INNOTECH products can be purchased at:



Orders: service@chromascape.com • 888.421.0010

