

**Innotech Solvent Seal 30**

SDS Number:

Revision Date: 6/23/2019

Page 1 of 6

**1 PRODUCT AND COMPANY IDENTIFICATION**

**Manufacturer**

ChromaScape  
 2055 Enterprise Pkwy  
 Twinsburg, OH 44087

**Contact:** Chemtrec:1-800-424-9300  
**Phone:** 330-998-7574  
**Web:** www.chromascape.com

**Product Identifier:** Innotech Solvent Seal 30  
**Synonyms:** Solvent Sealer  
**Revision Date:** 6/23/2019  
**Version:** 2.0  
**CAS Number:** Mixture  
**Chemical Family:** Flammable solvent  
**Product Use:** Concrete sealer

**2 HAZARDS IDENTIFICATION**

**Classification of the Substance or Mixture**

**GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**

- Physical, Flammable Liquids, 3
- Health, Aspiration hazard, 1
- Health, Skin corrosion/irritation, 2
- Health, Serious Eye Damage/Eye Irritation, 2 A
- Health, Acute toxicity, 3 Inhalation
- Health, Specific target organ toxicity - Single exposure, 3
- Health, Germ cell mutagenicity, 1
- Health, Carcinogenicity, 2
- Health, Reproductive toxicity, 1
- Health, Specific target organ toxicity - Repeated exposure, 2
- Environmental, Hazards to the aquatic environment - Acute, 2

**GHS Label Elements, Including Precautionary Statements**

**GHS Signal Word:** **DANGER**

**GHS Hazard Pictograms:**



**GHS Hazard Statements:**

- H226 - Flammable liquid and vapor
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H331 - Toxic if inhaled
- H335 - May cause respiratory irritation
- H336 - May cause drowsiness or dizziness
- H340 - May cause genetic defects
- H351 - Suspected of causing cancer
- H360 - May damage fertility or the unborn child
- H373 - May cause damage to organs through prolonged or repeated exposure
- H401 - Toxic to aquatic life

**GHS Precautionary Statements:**

**Innotech Solvent Seal 30**

SDS Number:

Revision Date: 6/23/2019

Page 2 of 6

- P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 - Keep container tightly closed.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 - Wash skin thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P281 - Use personal protective equipment as required.
- P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331 - Do NOT induce vomiting.
- P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P311 - Call a POISON CENTER or doctor/physician.
- P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P332+313 - If skin irritation occurs: Get medical advice/attention.
- P362 - Take off contaminated clothing and wash before reuse.
- P370+378 - In case of fire: Use Use dry sand, dry chemical, or alcohol-resistant foam for extinction for extinction.
- P403+233 - Store in a well ventilated place. Keep container tightly closed.
- P403+235 - Store in a well ventilated place. Keep cool.
- P501 - Dispose of contents/container in accordance with local/federal regulations.

**Hazards not Otherwise Classified (HNOC) or not Covered by GHS**

- Route of Entry:** Eyes, skin, ingestion
- Target Organs:** Skin, eyes, central nervous system

**3 COMPOSITION/INFORMATION OF INGREDIENTS**

**4 FIRST AID MEASURES**

**Skin Contact:**

**Emergency First Aid Procedures**

- Skin:** Clean material from skin with acetone, then wash with soap and water followed by moisturizer. If irritation persists, contact a physician.
- Eyes:** Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Remove contact lenses if able. Call a physician if irritation persists.
- Inhalation:** Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention.
- Ingestion:** DO NOT INDUCE VOMITING. Give large quantities of water. Do not give milk or alcoholic beverages. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

**5 FIRE FIGHTING MEASURES**

**Suitable Extinguishing Media:** Dry chemical, CO2, alcohol-resistant foam

**Unsuitable Extinguishing Media:** High-volume water jet

**Flash Point (TCC):** 0° F

**Flammable Limits (% volume in air for solvents):** LEL=1.0 UEL=13.0

**Special Fire Fighting Procedures:** Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources. Do not allow runoff from firefighting to enter drains or water courses.

**Innotech Solvent Seal 30**

SDS Number:

Revision Date: 6/23/2019

Page 3 of 6

**6 ACCIDENTAL RELEASE MEASURES**

**Steps to Take if Material is Released or Spilled:** No health effects expected from the clean-up of the material if contact can be avoided. Follow the protection information found in Section 8 of this SDS. Ventilate the contaminated area. Prevent the spread of spilled material by using a suitable absorbent material or sand dam.

**7 HANDLING AND STORAGE**

**Handling Precautions:**

**Normal Handling:** Always use good industrial hygiene practices and safety guidelines.  
**Storage:** Store material in its original container. Keep containers tightly closed when not in use. Keep material away from open flame, sparks, or other sources of heat and ignition.  
**Waste Disposal Method:** Liquid material is an ignitable waste (D001). Dispose of material in accordance with federal, state, and local guidelines.  
**Special Precautions:** Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld on or near the containers.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Personal Protective Equipment:**

**Respiratory Protection:** Use NIOSH-approved organic vapor respirator when exposure levels can't be kept below limits.  
**Ventilation:** Provide adequate mechanical ventilation to keep exposure levels below TLV's.  
**Protective Gloves:** Wear impervious chemical gloves.  
**Eye Protection:** Wear chemical safety glasses.  
**Other Protective Clothing or Equipment:** As needed to prevent repeated/prolonged contact.  
**Work/Hygienic Practices:** Use only in adequately-ventilated area unless recommended respiratory protection is used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Clear liquid  
**Odor:** Aromatic hydrocarbon  
**Odor Threshold:** 0.07 ppm  
**pH:** None  
**Freezing/Melting Point:** -76° F  
**Boiling Point:** 154° F  
**Flash Point:** 106° F  
**Evaporation Rate:** 0.15 (butyl acetate = 1)  
**Flammability (solid, gas):** Flammable Liquid  
**Lower/Upper Flammability:** 1.0-7.0  
**Vapor Pressure:** 2.5 mm of Hg at 20° C  
**Vapor Density:** 4.3  
**Relative Density:** 0.94 g/cc  
**Solubility:** <1% w/w in water  
**Partition Coefficient:** No data available  
**Auto-ignition Temperature:** 462° C  
**Decomposition temperature:** No data available  
**Viscosity:** 100 centipoise

**Innotech Solvent Seal 30**

SDS Number:

Revision Date: 6/23/2019

Page 4 of 6

**10 STABILITY AND REACTIVITY**

**Chemical Stability:**                      Reactivity:                                      Stable  
 Conditions to avoid:                      Prevent vapor accumulation. Avoid heat and flames.  
 Incompatibility (Materials to Avoid):                      Strong oxidizers.  
 Hazardous Decomposition (Byproducts):                      Carbon monoxide and carbon dioxide.  
 Hazardous Polymerization:                      Should not occur.

**11 TOXICOLOGICAL INFORMATION**

**Routes of Exposure:** Inhalation, Ingestion, eyes, and Skin.

**Acute Toxicity Lethal Doses (ATE):**

LC50 (inhl) 6.7 mg/l  
 LD50 (oral) 6978 mg/kg  
 LD50 (skin) 6536 mg/kg

**Health Hazards:**

**Acute:** May cause eye, skin, gastrointestinal, and lung irritation. May cause central nervous system depression.  
**Chronic:** Prolonged and repeated exposures to high concentrations may cause hearing loss. May cause anemia, decreased blood cell count, and bone marrow hypoplasia. Liver and kidney damage may occur.

**Skin Contact:** May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin which may result in a burning sensation and a dried, cracked appearance.

**Eye Contact:** May cause redness, tearing, and irritation of the eyes. Direct contact may cause permanent eye damage.

**Inhalation:** May cause headache, nausea, dizziness, and loss of coordination. Continued inhalation may result in unconsciousness and death.

**Ingestion:** May be harmful if swallowed. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.

**Carcinogen:** Contains ingredients suspected of causing cancer in humans:

Light Solvent Naphtha	64742-95-6	(IARC Group 2B)
Cumene	98-82-8	(IARC Group 2B)

**Aggravation of Pre-existing Conditions:** Persons with pre-existing skin, eye, or lung disorders may be more susceptible to the effects of the substance.

**12 ECOLOGICAL INFORMATION**

**Acute Toxicity to Fish:** LC50 8.4 mg/L (calculated)

**Acute Toxicity to Aquatic Invertebrates:** LC50 4.2 mg/L (calculated)

**Toxicity to Aquatic Plants:** EC50 3.2 mg/L (calculated)

**Toxicity to Microorganisms:** No data available

**Chronic Toxicity to Fish:** No data available

**Chronic Toxicity to Aquatic Invertebrates:** No data available

**Persistence and Degradability:** Expected to degrade readily and rapidly in the presence of oxygen

**Bioaccumulation Potential:** This material is not expected to bioaccumulate

**Mobility in the Soil:** Expected to move slowly in soil and water

**Other Adverse Effects:** None established

**13 DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Liquid material is an ignitable waste (D001). Dispose of material in accordance with all Federal, State, and Local regulations.

**Innotech Solvent Seal 30**

SDS Number:

Revision Date: 6/23/2019

Page 5 of 6

**14 TRANSPORT INFORMATION**

Not classified

**For all modes:**

**Proper Shipping Name:** PAINT

**Hazard Class:** 3

**UN:** UN1263

**Packing Group:** PGII

**Marine Pollutant:** No

**15 REGULATORY INFORMATION**

**SARA 311/312:** Yes. (Fire, Acute, Chronic).

**OSHA:** This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200).

**TSCA:** Components of this material are either listed or are exempt from the EPA TSCA Inventory of Chemical Substances.

<b>California Proposition 65:</b>	WARNING! This product contains a chemical known to the State of California to cause cancer.		
	98-82-8	Cumene	
	71-43-2	Benzene	
	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.		
	71-43-2	Benzene	
	117-81-7	bis(2-Ethylhexyl) phthalate	
<b>Massachusetts Right To Know:</b>	25551-13-7	Benzene, Trimethyl-	33.0 - 39.8
	95-63-6	1,2,4-Trimethylbenzene	19.5 - 27.0
	98-82-8	Cumene	3.0 - 6.6
	1330-20-7	Mixed Xylenes	0.7 - 3.3
	117-81-7	bis(2-Ethylhexyl) phthalate	0.1 - 0.14
	Proprietary	Glycol Ether	2.0 - 2.8
<b>Pennsylvania Right To Know:</b>	64742-95-6	Light Solvent Naphtha	39.0 - 66.5
	Proprietary	Solvent Naphtha	0.5 - 0.9
	25551-13-7	Benzene, Trimethyl-	33.0 - 39.8
	95-63-6	1,2,4-Trimethylbenzene	19.5 - 27.0
	98-82-8	Cumene	3.0 - 6.6
	1330-20-7	Mixed Xylenes	0.7 - 3.3
	117-81-7	bis(2-Ethylhexyl) phthalate	0.1 - 0.14
	Proprietary	Glycol Ether	2.0 - 2.8
<b>New Jersey Right To Know:</b>	64742-95-6	Light Solvent Naphtha	39.0 - 66.5
	Proprietary	Solvent Naphtha	0.5 - 0.9
	25551-13-7	Benzene, Trimethyl-	33.0 - 39.8
	95-63-6	1,2,4-Trimethylbenzene	19.5 - 27.0
	98-82-8	Cumene	3.0 - 6.6
	1330-20-7	Mixed Xylenes	0.7 - 3.3
	25155-15-1	Cymenes	0.7 - 1.0
	117-81-7	bis(2-Ethylhexyl) phthalate	0.1 - 0.14
	Proprietary	Glycol Ether	2.0 - 2.8

**16 OTHER INFORMATION**

The information on this SDS is provided in good faith in the interest of product safety and believed to be accurate to the best of our knowledge. However, ChromaScape makes no guarantee and assumes no liability for the data contained. Users should conduct their own research regarding suitability for their purposes. Nothing contained in this SDS should be

---

**Innotech Solvent Seal 30**

SDS Number:

Revision Date: 6/23/2019

Page 6 of 6

misconstrued as permission to violate any regulation. End users should follow all local, state, national and international regulations as apply.

Revision Date: 6/23/2019