

## Sealer Additives

### INNOTECH® SURETRAC

INNOTECH SURETRAC is a polymeric grit coating additive to provide traction to sealed surfaces in slippery conditions and is used as an anti-skid additive generally used for kitchen floors, commercial entry areas, steep inclines, pool and spa decks, for example.

### INNOTECH FLATTENING AGENT

INNOTECH FLATTENING AGENT is primarily used in solvent-based sealers to reduce the level of gloss. This product may also be used to create a gel consistency of INNOTECH STAIN for use with stencils.

### INNOTECH TINT CONCENTRATE - SB

INNOTECH TINT CONCENTRATE - SB (solvent-based) is a color additive to tint INNOTECH Solvent-Based Sealers.

## INNOTECH® SURETRAC

### Product Features and Benefits

INNOTECH SURETRAC is a polymeric grit coating additive to provide traction to sealed surfaces in slippery conditions and is used as an anti-skid additive generally used for kitchen floors, commercial entry areas, steep inclines, pool and spa decks, for example.

### Prior to Application

- INNOTECH SURETRAC, in a previously applied coating, may contribute to slight foaming due to the grit in the surface. Subsequent coats should be applied smoothly with minimal agitation on the floor.
- Porous surfaces should be sealed prior to application of sealers treated with INNOTECH SURE TRAC. Sealing the surface helps to ensure that there will be enough coating on the surface to help encapsulate the product.
- Add product into the sealer slowly and stir thoroughly. For water-based sealers, add 11 ounces by volume of INNOTECH SURE TRAC product per gallon of sealer. For solvent-based sealers, add 7.5 ounces by volume of INNOTECH SURE TRAC product per gallon of sealer.
- Remove one fifth of the sealer, not to exceed one gallon, and place in a clean container. Add the proper amount of INNOTECH SURE TRAC to the separated INNOTECH sealer with a mechanical paddle mixer. **DO NOT MIX BY HAND!** INNOTECH SURE TRAC should be added slowly and evenly to avoid lumps.
- There should not be any visible lumps or agglomerations in the sealer during or after addition of INNOTECH SURE TRAC product. Mix until INNOTECH SURE TRAC product is fully incorporated into separated portion of INNOTECH sealer.
- Slowly add separated mixed sealer back into the remaining sealer and mix by hand with a stirring stick. Mix until the entire amount of INNOTECH sealer is of consistent color and no lumps or agglomerations are present.
- Let the sealer rest uncovered for 10- to 15-minutes to de-gas. Avoid having the sealer de-gas in direct sunlight or where temperatures are above 90 °F.

### Product Application

Please reference to the corresponding sealer TECHNICAL BULLETIN for application guidelines. Important: Some low-pressure pump-up sprayers may not be able to spray INNOTECH sealers with INNOTECH SURE TRAC product due to the increase in solids content.

- Apply the sealer as evenly as possible.
- Frequent mild stirring of the sealer with added INNOTECH SURE TRAC product is recommended during application to assure even dispersion of the grit additive.
- When utilizing a grit additive, such as INNOTECH SURE TRAC or INNOTECH EXTRA SURE TRAC, apply the INNOTECH Sealer with a roller.
- An additional thin coat of sealer without INNOTECH SURE TRAC product may be applied over sealer containing the grit additive. This additional thin coat may help trap the grit additive in the sealer and provide a surface that's easier to clean. However, slip resistance may decrease as a result.

### Coverage Information

- Water-Based Sealers: Add 11 ounces by volume, per gallon of sealer
- Solvent-Based Sealers: Add 7.5 ounces by volume, per gallon of sealer

### Available Packaging

INNOTECH SURETRAC is available in 1-quart and 1-gallon units.

### Product Shelf Life/Storage

Store INNOTECH SURETRAC indoors, away from heat or sunlight. Shelf life: 12 months.

## INNOTECH® FLATTENING AGENT

### Product Features and Benefits

INNOTECH FLATTENING AGENT is primarily used in solvent-based sealers to reduce the level of gloss. This product may also be used to create a gel consistency of INNOTECH STAIN for use with stencils.

### Prior to Application

- Prior to application, test INNOTECH Sealer with INNOTECH FLATTENING AGENT in an inconspicuous area to ensure compatibility and desired level of gloss.
- Remove one-fifth of the final amount of sealer to be flattened, not to exceed one gallon, and place in a clean container. Add the proper amount of product to the separated INNOTECH

sealer with a mechanical paddle mixer. DO NOT MIX BY HAND! INNOTECH FLATTENING AGENT should be added slowly and evenly to avoid lumps.

- Sealer will change from clear to cloudy as INNOTECH FLATTENING AGENT is incorporated. There should not be any visible lumps or agglomerations in the sealer during or after addition of INNOTECH FLATTENING AGENT.
- Mix until product is fully incorporated into separated portion of the INNOTECH sealer.
- Slowly add the separated, flattened INNOTECH sealer back into the remaining sealer, and mix by hand with a stirring stick. Mix until the entire amount of INNOTECH sealer is consistently cloudy and no lumps or agglomerations are present.
- Let the flattened INNOTECH sealer rest uncovered for 10 to 15 minutes to de-gas. Avoid having the sealer de-gas in direct sunlight or where temperatures are above 90 °F.

### Product Application

Please reference to the corresponding sealer TECHNICAL BULLETIN for application guidelines.

### Coverage Information

- To achieve a matte finish:
- 70 grams by weight, per gallon of sealer.
- 16 ounces by volume, per gallon of sealer.
- To achieve final gloss levels between matte and high gloss, lesser amounts of INNOTECH FLATTENING AGENT may be added to INNOTECH Sealers.

### Available Packaging

INNOTECH FLATTENING AGENT is available in 1-quart and 1-gallon units.

### Product Shelf Life/Storage

Store INNOTECH FLATTENING AGENT indoors, away from heat or sunlight. Shelf life: 12 months.

## INNOTECH® TINT CONCENTRATE SB

### Product Features and Benefits

INNOTECH TINT CONCENTRATE - SB (solvent-based) is mixed on site with any solvent-based INNOTECH SEALER (such as INNOTECH SOLVENT SEAL 25†) to create a colored translucent coating for enhancing or correcting colored, stamped or stained concrete. Available in any INNOTECH standard Color Hardener color - View the INNOTECH Color Hardener color chart for standard selections.

### Coverage Information

- 1 pint of tint colors to 5 gallons of sealer.

### Product Application

Please reference to the corresponding sealer TECHNICAL BULLETIN for application guidelines.

### Available Packaging

INNOTECH TINT CONCENTRATE is available in 1-pint units designed to tint five gallons of sealer.

### Product Shelf Life/Storage

Store INNOTECH TINT CONCENTRATE indoors, away from heat or sunlight. Shelf life: 12 months.

### Product Warranty

INNOTECH SEALER ADDITIVES are a proprietary products, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed or implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact INNOTECH with any questions regarding this policy.

*†PLEASE REFER TO CORRESPONDING TECHNICAL BULLETIN FOR PRODUCT AND APPLICATION DATA.*

INNOTECH SEALER ADDITIVES and other INNOTECH products are for professional use only.

INNOTECH products can be purchased at:



Orders: [service@chromascape.com](mailto:service@chromascape.com) • 888.421.0010