

Color Invigorate

INNOTECH COLOR INVIGORATE is a proprietary blend of water soluble cementitious and other coloring agents designed for the use in providing secondary color and/or highlighting to decorative stamped concrete, stampable overlay or any other concrete surface.

Product Features and Benefits

INNOTECH COLOR INVIGORATE ...

- Easy to use, mixes with water.
- Broom in or spray apply with pump up sprayer.
- Zero VOC.
- Available in 42 standard Color Hardener/Release Powder colors.
- Takes the headache out of applying secondary coloring to overlays.
- No messy clean up.

Prior to Application

- Surface to be treated must be clean and free of any curing agents, dirt, dust, debris or other contaminants that may interfere with the proper adhesion of Innotech Color Invigorate.
- If Innotech Color Invigorate is to be applied to a non-textured surface, a minimal surface profiling is required to insure proper bonding to the nontextured surface. A profile equal to the ICRI CSP-1 profile is recommended.

Required Tools and Equipment

- Soft flagged tip broom.
- Pump-up sprayer.

Mixing Instructions

- Pour one gallon of clean potable water into a clean five-gallon bucket.
- Mix in 6 ounces of Innotech Color Invigorate into the water and mix thoroughly until product is completely dissolved.

Product Application

Option #1

- Lightly pre wet the surface to be treated with Color Invigorate with water to assist in the distribution of material.
- Apply Innotech Color Invigorate that has been mixed to entire surface as a color wash, using a flagged tipped broom to massage Color Invigorate into or out of the low-lying areas as needed or desired.
- Should any brush marks remain after the initial application of Color Invigorate, immediately mist the surface with water and lightly broom to eliminate.

Option #2

- Lightly pre wet the surface to be treated with Innotech Color Invigorate with water to assist in the distribution of material.
- Apply Innotech Color Invigorate to entire surface area with pump-up sprayer, highlighting areas as desired.
- Use a soft flagged tip broom to back brush or move applied product into or out of low-lying areas as needed.
- Should any brush marks remain after the initial application of invigorate, immediately mist surface with water and lightly broom to eliminate.

Coverage Information

Innotech Color Invigorate will cover 2000-3000 sq. ft. per 3 lb. container.

Maintenance

INNOTECH highly recommends you develop and follow a schedule of routine maintenance for all colored concrete, so it maintains a quality appearance. Colored concrete installations should be routinely inspected, cleaned and resealed as required by the local conditions. Cleaning and resealing schedules will depend on a number of factors including, but not limited to, volume and intensity of traffic, maintenance procedures and weather.

Production Limitations

- Product should be applied when surface temperature is between 50-90 °F.
- Proper surface profiling is necessary for non-textured concrete surfaces. (See prior to application section)

Dry Time

- Drying times will vary depending on surface porosity, temperature, humidity and local conditions.
- Surface can be sealed 60 minutes after all the moisture has evaporated following the application.

Available Packaging

INNOTECH INVIGORATE is available in 1-gallon containers containing 3 pounds of powder.

Product Shelf Life/Storage

Shelf life: 24 months if unopened in the original container.

Product Handling

Prior to using INNOTECH INVIGORATE please reference the corresponding Safety Data Sheet to ensure safe handling. Always wear gloves and eye protection when handling product.

Product Warranty

INNOTECH INVIGORATE is a proprietary product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed or implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact INNOTECH with any questions regarding this policy.

PLEASE REFER TO CORRESPONDING TECHNICAL BULLETIN FOR PRODUCT AND APPLICATION DATA.

INNOTECH INVIGORATE and other INNOTECH products are for professional use only.

INNOTECH products can be purchased at:



Orders: service@chromascope.com • 888.421.0010